

FEATURES & SPECIFICATIONS

APPLICATION — The CEM Canopy light was designed for mid-level lighting under storefront awnings, or any surface mount general lighting application. The welded seams provide a smooth constructed look that can be integrated into any design concept. This fixture is perfect when a finished, rather than industrial appearance is needed.


CONSTRUCTION — The fixture is constructed of .12" thick extruded aluminum with a welded seam. The hinged door frame is constructed of extruded aluminum with mitered corners to fit the glass lens. A Polyethylene Foam gasket is used for a watertight seal.

FINISH – A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request.

OPTICAL SYSTEM — High quality faceted aluminum reflector. Flat glass and flat prismatic lenses available.

ELECTRICAL SYSTEM – Provided with a 4KV pulse rated socket assembly. Fixtures are available with a 50W-400W Metal Halide, and 400W HPS lamp and ballast system. Each 60HZ CWA multi-tap, 480V, or Fluorescent ballast is pre-wired and installed for convenience.

MOUNTING — Permanently mounted via four .25" mounting holes and hardware pack provided by Techlight. Two (2) .88" conduit entries are provided



Example: CEM175M-MT-F-WH

provided with a horizontal lamp.

representative for additional information


Custom RAL color matching is available. Contact your Techlight sale

3

Туре

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.



Catalog Number

Project

www.techlightusa.com