



Catalog Number	
Project	Type

Features & Specifications

Construction

Made with impact resistant, seamless aluminum housing and socket cover. The ICF was designed to withstand the abuse of a sports environment with minimal obstruction to the players.

Optical System

The fixture comes with a hammertone aluminum reflector centered to provide optimum performance with 88% reflectiveness and a symmetrical distribution.

Electrical System

Available only in 1000W Metal Halide with a remote CWA 5-Tap ballast. Each ballast is encapsulated in potting compound to reduce noise and heat, and then enclosed in a galvanized and powder coat painted steel weatherproof box. All ballasts come pre-tapped at highest available voltage (480V) unless specified otherwise.


Mounting

Cord or swivel pendant mount allows the fixture to hang true from a standard junction box. Upper and lower wire grips offer strain relief on cord hang model. A 20', 16/3 cord and junction box pendant mount (order stem separately) comes standard with each fixture.

Finish

A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard white finish on reflector and black finish on conical steel guard.

ICF SERIES Indirect Sports High Bay



DIMENSIONS

Est Shipping Weight: 18 lbs
(does not include remote ballast enclosure)



Please contact your Techlight Sales Representative for more information.

All dimensions subject to change without notice.

Ordering Nomenclature

Ex: (1000W Metal Halide, 5-Tap, = ICF1000-5)

ICF					
------------	--	--	--	--	--

SERIES	WATTAGE	BALLAST	VOLTAGE TAP	ACCESSORIES
ICF	1000 - 1000W Metal Halide	5 - 5-Tap ¹ <small>1- Fixture is pre-wired for 480V unless specified otherwise. Alternate voltages will require field adjustment.</small>	120 - 120 Volt 208 - 208 Volt 240 - 240 Volt 277 - 277 Volt 480 - 480 Volt <small>1-Available in 400W and 1000W MH Only</small>	(ORDER AS SEPARATE LINE ITEM) THBSPM = Swivel Pendant Mount THBSTEM* = "*" Stem <small>(* insert stem length needed in 6" increments from 18" up to 120")</small>