

FEATURES & SPECIFICATIONS

APPLICATION — Techlight's line of low bays was designed for light manufacturing, warehouse, retail, assembly lines, or production environments. The acrylic drop reduces shadows and provides a wide uniform distribution.

CONSTRUCTION – Heavy duty die cast aluminum housing with a white polyester powdercoat finish. Spun aluminum relfector and collar assembly. ETL and CETL Listed.


 $\ensuremath{\textbf{FINISH}}$ – A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: White. Custom colors¹ available upon request.

OPTICAL SYSTEM — The aluminum reflector focuses light downward on working surfaces. The drop lens spreads the downward light evenly in a wide symmetric pattern. Designed for mid to low range mounting heights.

ELECTRICAL SYSTEM – Available in 250W thru 400W standard metal halide, pulse-start metal halide, and high pressure sodium. Comes standard with a 4KV pulse rated mogul base socket. Each 60HZ CWA multi-tap² or 480V ballast is pre-wired and installed for convenience.

MOUNTING – Splice box for direct hard wire, hook, cord, and plug assembly, or pendant mount.





22.00" x 22.00"

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

Example: **TL22M-9-5-0**

22.00"

TL22M

TL22M							1		
Series] [Wattage/Source			Γ	La	mp		Options
TL22M	1 2 3 4 5 6 7 8 9 10	250W Metal Halide MT 250W Metal Halide 480V 250W PS Metal Halide 480V 250W PS Metal Halide 480V 320W PS Metal Halide MT 320W PS Metal Halide 480V 350W PS Metal Halide 480V 400W Metal Halide MT 400W Metal Halide 480V	11 12 13 14 15 16	400W PS Metal Halide MT 400W PS Metal Halide 480V 250W High Pressure Sodium MT 250W High Pressure Sodium 480V 400W High Pressure Sodium MT 400W High Pressure Sodiume 480V		2 MH 3 MH 4 MH 5 MH 5 MH 6 MH 7 HPS	250U 250UPS 320UPS 350UPS 400U 400UPS \$250 \$400	0 1 2 3 4 5 6	Mounting Hook Hook and 6' Cord 120V Hook, Cord and Plug 208V/240V Hook, Cord and Plug 277V Hook, Cord and Plug
Accessor	i es (Or	der as separate line items)							
THBH THBHC6 THBSPM THBSTEM18 THBSC1 THBSC6 THB22WG	18" Rigid 12" Refle	Cord ndant Mount Pendant ctor Safety Chain Pod Safety Chain			repres			ative fo	or matching is available. Contact your Techlight sale r additional information. 208/240/277V wired 277V unless specified otherwise.

www.techlightusa.com

TL22M 22" Low Bay

MOUNTING ACCESSORIES



THBSC1 12" Reflector Safety Chain



THBSPM Swivel Pendant Mount



THBSC6 6' Ballast Pod Safety Chain



ADDITIONAL FIXTURE ACCESSORIES







Techlight, Inc. 2707 Satsuma Drive Dallas, TX, 75229 Phone: 214-350-0591, 800-225-0727, Fax: 214-350-9137 www.techlight.com