Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

APPLICATION — The DLG Canopy light was designed as a high performance canopy light for parking garages. The removable upper reflector allows for uplight when elimnated. It is segmented to allow the installer to direct the light specifically to the points of egress and away from a driver's direct line of sight.

CONSTRUCTION — The upper assembly is a heavy duty round die-cast aluminum housing. Tool-less entry to the optical assembly is provided for easy and quick maintenance. ETL listed.

FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request.

OPTICAL SYSTEM — The lower assembly is provided with a UV stabilized polycarbonate lens to reduce yellowing and provide vandal resistance. A removable upper reflector allows for uplight when eliminated. It can be provided in segments to allow the installer to direct the light specifically to the points of egress and away from a driver's direct line of sight.

ELECTRICAL SYSTEM — All HID lamp options are provided with a medium base 4KV rated socket. Available HID wattages are 70W through 175W pulse start metal halide and 70W through 150W high pressure sodium with standard magnetic high power factor ballasts. A 2-lamp x 42W PL fluorescent option is available in 120/277V. All electrical components come securely mounted to the housing for safety and convenience.

MOUNTING — The fixture comes standard with a "quick mount" The fixture is designed to hang independently while being installed. This frees the installers' hands to make critical wire connections with speed and ease. Designed to mount directly to a standard 4" junction box.

Deluxe Garage Canopy
DLG SERIES





Series	Housing Height	Diameter
DLG	12.25"	Ø16.00"

ORDERING INFORMATION

Example: **DLG5A1-BZ**

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

DLG _____ _____ - _____ - _____

Series	Wattage/Source	Voltage	Pulse-Start	Finish
DLG	**1A** 50W PS Metal Halide[1]	**1** Multi-Tap[2]	**PS** Pulse-Start	**BK** Black
	2A 70W PS Metal Halide	**2** 120V[1]		**BZ** Bronze
	2B 70W High Pressure Sodium	**3** 120V NPF[4]		**GR** US Green
	3A 100W PS Metal Halide			**WH** White
	3B 100W High Pressure Sodium			**SP** Special[5]
	4A 150W PS Metal Halide			
	4B 150W High Pressure Sodium			
	5A 175W Metal Halide			
	12A 42W Fluorescent 120V[3]			

NOTES
1. 50W PS Metal Halide model is only availabe in 120V. Order using the "2" voltage designation.
2. Multi-Tap is 120/208/240/277V wired 277V.
3. 42W Fluorsecnt model is only available in 120V. Order using the "1" voltage designation.
4. 120V NPF option is for High Pressure Sodium Models only.
5. Custom RAL color matching is available. Contact your Techlight sale representative for additional information.

Techlight
2009 Mckenzie Drive Suite 110, Carrolton, TX 75006
PH: 214.350.0591 FX: 214.350.9137

All dimensions and specifications are subject to change without notice.

REV: 20251208-04