TECHLIGHT
INNOVATION IN ILLUMINATION

TDB3W SERIES

Genesis Gen2 120V Medium LED Burial Light

Catalog Number	
Project	Type

SERIES	HOUSING HEIGHT	DIAMETER
TDB3W	12.8”	9.7””

FEATURES & SPECIFICATIONS

APPLICATION —The Genesis Gen2 line of LED Lanscape Bullets are the most versatile LED fixtures on the market today. Various beam spreads and wattages allow for a customized finish to any property. The high end residential grade system was designed for low voltage operation residential applcations.

CONSTRUCTION — The housing is made of compression molded fiber reinforced polyester composite. The color impregnated SR2 composite will not flake or peal. The LED light source is housed within a aluminum LED body with heat dissipating fins. An anti-siphon chamber is molded into the housing to keep internal electrical components from coming into contact with ground water. Multiple ring/guard assemblies are available for a customized finish.

OPTICAL SYSTEM — Techlight’s proprietary OpticapSystem™ utilizes interchangeable optical lenses & reflectors to increase fixture lumen output efficiency. The system is provided with a high performance convex lenticular prismatic flood or a plano-convex spot optical lenses are molded from low iron tempered glass. A 96% reflective UV stabilized injection molded reflector is included with each system. A variety of glass color filters are available to meet the designers specific color control needs. The composite guard rotates 360° for glare control.

ELECTRICAL SYSTEM — NOTE: A Techlight Surge Protector must be incorporated into the LED system at the beginning of each circuit as a minimum. Failure to do so will void the system warranty. Fixture operates at 120V input voltage. Nominal open circuit current .15 amps. A 17 watt LED source provides approximately 1086 (CW) Lumens of light. System is compatible with the use of a rotary TRIAC Dimmer.

MOUNTING — Fixtures are designed to be in-ground burial lights and should be installed according to the installation instructions made available by Techlight. Proper drainage and substrate must be provided for water to flow freely through the well sleeve. A ¾” conduit entry is supplied into the anti-siphon chamber of the housing. Conrete pour kits available (see Accessories).

LISTINGS — ETL listed for wet locations (IP67). Meets US and Canadian safety standards. -40°C to 40°C ambient operation.

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

EXAMPLE:
TDB3W FL 17 NW 120 CR CL

TDB3W						
SERIES	DISTRIBUTION	WATTAGE	COLOR TEMP	VOLTAGE	RING/GUARD	LENS
	FL = Flood (60°) **SP** = Spot (20°)	**17** = 17W	**CW** = Cool White **NW** = Neutral White **WW** = Warm White	**120** = 120V	**CR = Composite Ring** **SR = Stainless Steel Ring** **CG = Composite Guard**	**FL = Flat Lens** **CL = Convex Lens** **SL = Slip Resistant Lens**

ACCESSORIES (Order as separate line items)

102552[1]	10kV Surge Protector
PK3	Concrete Pour Kit
TDB3AFD	TDB3W Anti Floatation Device

NOTES

1 = A Techlight Surge Protector must be incorporated into the LED system at the beginning of each circuit as a minimum. Failure to do so will void the system warranty.

AVAILABLE FIXTURE DIMENSIONS

Dimensions shown are for fixture bodies only. Mounting ptions must be ordered separately.



FIXTURE TRIM OPTIONS

Composite Ring

Stainless Steel Ring

Composite Guard

Flat Lens

Convex Lens

Slip Resistant Lens

Buy American Act & the American Recovery and Reinvestment Act

www.techlight.com

TDB3W Genesis Gen2 120V Medium LED Burial Light

ADDITIONAL FIXTURE ACCESSORIES

GL2CAPCVXFLDREFL
60° Flood OpticapSystem™
Field Installable Flood Optic

Change the optic on the job by simply swapping the OpticapSystem™ on any fixture

102552[1]
10kV Surge Protector

TDB2AFD
TDB3W Anti Floatation Device

LEDLFG120LENS
Green Glass Lens Filter (each)



PK3
Concrete Pour Kit

GL2CAPSPOPTREFL
20° Spot OpticapSystem™
Field Installable Spot Optic

Change the optic on the job by simply swapping the OpticapSystem™ on any fixture

TLHB800RCH
Digital Timer

PSJ183
18 Gauge Lead Wire (Color Coded)

LEDLB120LENS
Blue Glass Lens Filter (each)



PERFORMANCE

ILLUMINANCE CONE DIAGRAMS

ILLUMINANCE CONE DIAGRAM

TDB3WFL17CW120

Flood Optic

17W TDB3W LED
Color Temperature: 5,900 K



ILLUMINANCE CONE DIAGRAM

TDB3WSP17CW120

Spot Optic

17W TDB3W LED
Color Temperature: 5,900 K



*Deliverd lumens shown do not include light loss due to the fixture grill or lens.

Fixture	Color Temp	30W Lumen Output	
		FL	SP
TDB3W	CW (5900K)	1086	1171
	NW (4000K)	1039	1119
	WW (3000K)	1022	1101